


Technical Data		
Transition ratio	i=	52
Output torque	Md=	750Nm
Oil grade	e.g.	Mobil Glygoyle He 460
Oil quantity	approx.	1.75 Liter
Weight	approx.	48.5 Kg
② Shaft key		DIN6885 Bl.1
① Internal teeth	DIN54.80	N60x2x28x9H



	Toleranzklasse für Schweißkonstruktionen. DIN EN ISO 13920 - A		Gewicht	Position	-	Menge	-																																																																																																																																																																																																																																																								
	Toleranzklasse für Spanende Bearbeitung. DIN ISO 2768-m		-	-	-	-	-																																																																																																																																																																																																																																																								
Marx GmbH & Co.KG Lilienthalstr. 6-13 D - 58638 Iserlohn	<table border="1"> <tr> <td>0.1</td><td>0.2</td><td>0.3</td><td>0.4</td><td>0.5</td><td>0.6</td><td>0.7</td><td>0.8</td><td>0.9</td><td>1.0</td><td>1.2</td><td>1.5</td><td>2.0</td><td>2.5</td><td>3.0</td><td>4.0</td><td>5.0</td><td>6.3</td><td>8.0</td><td>10</td><td>12.5</td><td>16</td><td>20</td><td>25</td><td>31.5</td><td>40</td><td>50</td><td>63</td><td>80</td><td>100</td><td>125</td><td>160</td><td>200</td><td>250</td><td>315</td><td>400</td><td>500</td><td>630</td><td>800</td><td>1000</td><td>1250</td><td>1600</td><td>2000</td><td>2500</td><td>3150</td><td>4000</td><td>5000</td><td>6300</td><td>8000</td><td>10000</td> </tr> <tr> <td>±0.1</td><td>±0.15</td><td>±0.2</td><td>±0.25</td><td>±0.3</td><td>±0.35</td><td>±0.4</td><td>±0.45</td><td>±0.5</td><td>±0.55</td><td>±0.6</td><td>±0.65</td><td>±0.7</td><td>±0.75</td><td>±0.8</td><td>±0.85</td><td>±0.9</td><td>±0.95</td><td>±1.0</td><td>±1.05</td><td>±1.1</td><td>±1.15</td><td>±1.2</td><td>±1.25</td><td>±1.3</td><td>±1.35</td><td>±1.4</td><td>±1.45</td><td>±1.5</td><td>±1.55</td><td>±1.6</td><td>±1.65</td><td>±1.7</td><td>±1.75</td><td>±1.8</td><td>±1.85</td><td>±1.9</td><td>±1.95</td><td>±2.0</td><td>±2.05</td><td>±2.1</td><td>±2.15</td><td>±2.2</td><td>±2.25</td><td>±2.3</td><td>±2.35</td><td>±2.4</td><td>±2.45</td><td>±2.5</td><td>±2.55</td><td>±2.6</td><td>±2.65</td><td>±2.7</td><td>±2.75</td><td>±2.8</td><td>±2.85</td><td>±2.9</td><td>±2.95</td><td>±3.0</td><td>±3.05</td><td>±3.1</td><td>±3.15</td><td>±3.2</td><td>±3.25</td><td>±3.3</td><td>±3.35</td><td>±3.4</td><td>±3.45</td><td>±3.5</td><td>±3.55</td><td>±3.6</td><td>±3.65</td><td>±3.7</td><td>±3.75</td><td>±3.8</td><td>±3.85</td><td>±3.9</td><td>±3.95</td><td>±4.0</td><td>±4.05</td><td>±4.1</td><td>±4.15</td><td>±4.2</td><td>±4.25</td><td>±4.3</td><td>±4.35</td><td>±4.4</td><td>±4.45</td><td>±4.5</td><td>±4.55</td><td>±4.6</td><td>±4.65</td><td>±4.7</td><td>±4.75</td><td>±4.8</td><td>±4.85</td><td>±4.9</td><td>±4.95</td><td>±5.0</td><td>±5.05</td><td>±5.1</td><td>±5.15</td><td>±5.2</td><td>±5.25</td><td>±5.3</td><td>±5.35</td><td>±5.4</td><td>±5.45</td><td>±5.5</td><td>±5.55</td><td>±5.6</td><td>±5.65</td><td>±5.7</td><td>±5.75</td><td>±5.8</td><td>±5.85</td><td>±5.9</td><td>±5.95</td><td>±6.0</td><td>±6.05</td><td>±6.1</td><td>±6.15</td><td>±6.2</td><td>±6.25</td><td>±6.3</td><td>±6.35</td><td>±6.4</td><td>±6.45</td><td>±6.5</td><td>±6.55</td><td>±6.6</td><td>±6.65</td><td>±6.7</td><td>±6.75</td><td>±6.8</td><td>±6.85</td><td>±6.9</td><td>±6.95</td><td>±7.0</td><td>±7.05</td><td>±7.1</td><td>±7.15</td><td>±7.2</td><td>±7.25</td><td>±7.3</td><td>±7.35</td><td>±7.4</td><td>±7.45</td><td>±7.5</td><td>±7.55</td><td>±7.6</td><td>±7.65</td><td>±7.7</td><td>±7.75</td><td>±7.8</td><td>±7.85</td><td>±7.9</td><td>±7.95</td><td>±8.0</td><td>±8.05</td><td>±8.1</td><td>±8.15</td><td>±8.2</td><td>±8.25</td><td>±8.3</td><td>±8.35</td><td>±8.4</td><td>±8.45</td><td>±8.5</td><td>±8.55</td><td>±8.6</td><td>±8.65</td><td>±8.7</td><td>±8.75</td><td>±8.8</td><td>±8.85</td><td>±8.9</td><td>±8.95</td><td>±9.0</td><td>±9.05</td><td>±9.1</td><td>±9.15</td><td>±9.2</td><td>±9.25</td><td>±9.3</td><td>±9.35</td><td>±9.4</td><td>±9.45</td><td>±9.5</td><td>±9.55</td><td>±9.6</td><td>±9.65</td><td>±9.7</td><td>±9.75</td><td>±9.8</td><td>±9.85</td><td>±9.9</td><td>±9.95</td><td>±10.0</td> </tr> </table>	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.2	1.5	2.0	2.5	3.0	4.0	5.0	6.3	8.0	10	12.5	16	20	25	31.5	40	50	63	80	100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000	5000	6300	8000	10000	±0.1	±0.15	±0.2	±0.25	±0.3	±0.35	±0.4	±0.45	±0.5	±0.55	±0.6	±0.65	±0.7	±0.75	±0.8	±0.85	±0.9	±0.95	±1.0	±1.05	±1.1	±1.15	±1.2	±1.25	±1.3	±1.35	±1.4	±1.45	±1.5	±1.55	±1.6	±1.65	±1.7	±1.75	±1.8	±1.85	±1.9	±1.95	±2.0	±2.05	±2.1	±2.15	±2.2	±2.25	±2.3	±2.35	±2.4	±2.45	±2.5	±2.55	±2.6	±2.65	±2.7	±2.75	±2.8	±2.85	±2.9	±2.95	±3.0	±3.05	±3.1	±3.15	±3.2	±3.25	±3.3	±3.35	±3.4	±3.45	±3.5	±3.55	±3.6	±3.65	±3.7	±3.75	±3.8	±3.85	±3.9	±3.95	±4.0	±4.05	±4.1	±4.15	±4.2	±4.25	±4.3	±4.35	±4.4	±4.45	±4.5	±4.55	±4.6	±4.65	±4.7	±4.75	±4.8	±4.85	±4.9	±4.95	±5.0	±5.05	±5.1	±5.15	±5.2	±5.25	±5.3	±5.35	±5.4	±5.45	±5.5	±5.55	±5.6	±5.65	±5.7	±5.75	±5.8	±5.85	±5.9	±5.95	±6.0	±6.05	±6.1	±6.15	±6.2	±6.25	±6.3	±6.35	±6.4	±6.45	±6.5	±6.55	±6.6	±6.65	±6.7	±6.75	±6.8	±6.85	±6.9	±6.95	±7.0	±7.05	±7.1	±7.15	±7.2	±7.25	±7.3	±7.35	±7.4	±7.45	±7.5	±7.55	±7.6	±7.65	±7.7	±7.75	±7.8	±7.85	±7.9	±7.95	±8.0	±8.05	±8.1	±8.15	±8.2	±8.25	±8.3	±8.35	±8.4	±8.45	±8.5	±8.55	±8.6	±8.65	±8.7	±8.75	±8.8	±8.85	±8.9	±8.95	±9.0	±9.05	±9.1	±9.15	±9.2	±9.25	±9.3	±9.35	±9.4	±9.45	±9.5	±9.55	±9.6	±9.65	±9.7	±9.75	±9.8	±9.85	±9.9	±9.95	±10.0	Datum	Name	<b>MX-1-60-V</b> <b>Planetengetriebe</b>	Blatt	-
0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.2	1.5	2.0	2.5	3.0	4.0	5.0	6.3	8.0	10	12.5	16	20	25	31.5	40	50	63	80	100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000	5000	6300	8000	10000																																																																																																																																																																																																														
±0.1	±0.15	±0.2	±0.25	±0.3	±0.35	±0.4	±0.45	±0.5	±0.55	±0.6	±0.65	±0.7	±0.75	±0.8	±0.85	±0.9	±0.95	±1.0	±1.05	±1.1	±1.15	±1.2	±1.25	±1.3	±1.35	±1.4	±1.45	±1.5	±1.55	±1.6	±1.65	±1.7	±1.75	±1.8	±1.85	±1.9	±1.95	±2.0	±2.05	±2.1	±2.15	±2.2	±2.25	±2.3	±2.35	±2.4	±2.45	±2.5	±2.55	±2.6	±2.65	±2.7	±2.75	±2.8	±2.85	±2.9	±2.95	±3.0	±3.05	±3.1	±3.15	±3.2	±3.25	±3.3	±3.35	±3.4	±3.45	±3.5	±3.55	±3.6	±3.65	±3.7	±3.75	±3.8	±3.85	±3.9	±3.95	±4.0	±4.05	±4.1	±4.15	±4.2	±4.25	±4.3	±4.35	±4.4	±4.45	±4.5	±4.55	±4.6	±4.65	±4.7	±4.75	±4.8	±4.85	±4.9	±4.95	±5.0	±5.05	±5.1	±5.15	±5.2	±5.25	±5.3	±5.35	±5.4	±5.45	±5.5	±5.55	±5.6	±5.65	±5.7	±5.75	±5.8	±5.85	±5.9	±5.95	±6.0	±6.05	±6.1	±6.15	±6.2	±6.25	±6.3	±6.35	±6.4	±6.45	±6.5	±6.55	±6.6	±6.65	±6.7	±6.75	±6.8	±6.85	±6.9	±6.95	±7.0	±7.05	±7.1	±7.15	±7.2	±7.25	±7.3	±7.35	±7.4	±7.45	±7.5	±7.55	±7.6	±7.65	±7.7	±7.75	±7.8	±7.85	±7.9	±7.95	±8.0	±8.05	±8.1	±8.15	±8.2	±8.25	±8.3	±8.35	±8.4	±8.45	±8.5	±8.55	±8.6	±8.65	±8.7	±8.75	±8.8	±8.85	±8.9	±8.95	±9.0	±9.05	±9.1	±9.15	±9.2	±9.25	±9.3	±9.35	±9.4	±9.45	±9.5	±9.55	±9.6	±9.65	±9.7	±9.75	±9.8	±9.85	±9.9	±9.95	±10.0																																																									
Bearb.																																																																																																																																																																																																																																																															
Gepr.																																																																																																																																																																																																																																																															
1:2.5	Schutzvermerk nach <b>DIN 34</b> beachten	Dateiname			Blatt -																																																																																																																																																																																																																																																										